

ALUMINUM TANKER (Wide body)

Standard Features

All Aluminum body	(2) Compartments forward rear wheels
Box pan style doors w/"D"ring door latches	S.S. fenderettes w/complete rounded wheel well liners
Removable rub rails spaced away from body	(1) Hose bed divider
Aluminum hose bed floor	Hose bed access ladder full height-rear
All stepping surfaces NFPA compliant "aggressive" aluminum diamond plate	2000 gallon UPF Poly Tank® II E
3 – 36" telescoping chutes, manually operated	3-Newton dump valves, manually operated
(1) Class 1 water level gauge at rear panel	2 – 2½" rear panel tank fills (Akron valves for ease in operation and maintenance
Master battery disconnect switch	D.O.T. approved ICC lighting, reflectors, and back-up alarm
NFPA complaint warning lights, step and under body lights	Compartment lighting with "Open Door" indicator light in cab
NFPA compliant white reflective stripe (4")	Body painted to match cab or customer preference
Gold Metallic vinyl lettering	Compartments, gray spatter paint
Complete body undercoating and mud flaps behind rear wheels	

Options

Narrow pumper style bodies	Tank sizes 1500 gallons to 3500 gallons
Portable pumps: Waterous, Darley, C.E.T., Honda, Hale	Portable pumps mounted in compartment or rear step
Portable pumps plumbed to tank	PTO pumps: Waterous, Darley, Hale in numerous sizes
Newton Electric operated dump valves	Newton air operated dump valves
Newton S.S. dump valves-manual, electric, or air operated	Aluminum diamond plate or S.S. manual flip down extension chute or automatic flip down extension chute
Portable tank racks at side or overhead-manual or electric/hydraulic	Portable tank compartment(s) slide in rear next to tank with rear door
Additional water level gauge readouts	Numerous warning light options
MC Products, Fire Research water level readouts	Kussmaul air and electric auto ejects
Numerous scene lighting options (12 volt or 110)	Adjustable trays or rollout trays in compartments
Kussmaul battery conditioners/chargers	
Roll up doors	